- 1. Open Internet Explorer.
- 2. Click on the "Tools" menu at the top of the Explorer window.
- 3. Click on "Internet Options" at the bottom of the "Tools" pull down menu.
- 4. Click on the "Connections" tab (Figure 1).
- 5. Click on the "Midwest Internet" Dial-Up Network Setting (Figure 1).



(Figure 1)



(Figure 3)

- 6. Click on the "Settings" button (Figure 1).
- 7. Be sure "Automatically detect settings" box is *NOT* checked.
- 8. Check the box next to "Use automatic configuration script" (Figure 2)
- 9. Type in the "Address:" box: http://mw.net/mw.php
- 10. Click on the "OK" button (Figure 2).

Midwest Internet Settings	
Automatic conf Automatic conf use of manual	iguration iguration may override manual settings. To ensure the settings, disable automatic configuration. Ilv detect settings
Use automa	atic configuration <u>s</u> cript
Address	http://mw.net/mw.php
Proxy server -	
Use a proxy apply to oth	y server for this connection (These settings will not ner connections).
Addr <u>e</u> ss:	Port; Advanced
<u>Bypass</u>	proxy server for local addresses
Dial-up settings	•
User name:	user Properties
Password:	Advanced
<u>D</u> omain:	
	OK Cancel
(Figure 2)	

- 11. Click on the "Advanced" tab (Figure 3).
- Use the scroll bar to scroll down to the "HTTP 1.1 settings" (Figure 3)
 Make sure that the "Use HTTP 1.1" and the
- 13. Make sure that the "Use HTTP 1.1" and the "Use HTTP1.1 through proxy connections" boxes are both checked (Figure 3).
- 14. Click on the "OK" button.